

GUARDSTATION DUAL / GUARDSTATION QUAD

Salient’s Dual and Quad monitor GuardStation client workstations provide top performance for demanding security control room deployments. Designed for CompleteView VMS, GuardStation client systems provide the tools and capability to view live video, perform investigations and export evidence to a variety of media.

These innovative client workstations are designed to provide the highest performance for client applications in CompleteView’s VMS without the need for high capacity server processing. GuardStation is pre-loaded with CompleteView client software and ViewPoint screen monitoring software. Supporting either dual or quad monitor configuration in a desktop form factor, GuardStation offers flexibility and high performance in one location.

OVERVIEW	GuardStation Dual	GuardStation Quad
CPU	Intel Xeon	Intel Xeon
Memory	4GB	8GB
Windows OS	Windows 7 Embedded	Windows 7 Embedded
Power Supply	240W - 100VAC to 240VAC / 50HZ to 60HZ	290W - 100VAC to 240VAC / 50HZ to 60HZ



GUARDSTATION DUAL / GUARDSTATION QUAD

TECH SPECS

	GuardStation Dual	GuardStation Quad
Operating System	Windows 7 Embedded	Windows 7 Embedded - 64bit
Processor	Intel Xeon	Intel Xeon
Memory	4GB	8GB
Network	Integrated 10/100/1000Mbps NIC	Integrated 10/100/1000Mbps NIC
Hard Drive (OS)	500GB	500GB
Graphics Adapter	NVidia Quadro	2 NVidia Quadro
Video Display Ports	1 DisplayPort, 1 DVI-I	2 DisplayPort, 2 DVI-I
Max Supported Resolution (per monitor)	1080p	1080p
Video Output Options	2 DVI Ports (standard), 2 HDMI (optional), 2 VGA (optional)	2 DVI Ports (standard), 4 HDMI (optional), 4 VGA (optional)
Audio	Integrated	Integrated
DVD (internal)	8x DVD+/-RW	16x DVD+/-RW
USB Ports	2 USB 2.0 (front), 2 USB 2.0 (rear), 2 USB 3.0 (front), 4 USB 3.0 (rear)	2 USB 2.0 (front), 2 USB 2.0 (rear), 2 USB 3.0 (front), 4 USB 3.0 (rear)
Other Ports	1 Universal Audio Jack (front), 1 serial, 1 audio line out (rear)	1 Universal Audio Jack (front), 1 serial, 1 audio line out (rear)

CHASSIS FEATURES

Form Factor	Small Form Factor	Mini Tower
Height	11.42 inches (29 cm)	14.17 inches (36 cm)
Width	3.65 inches (9.3 cm)	6.88 inches (17.5 cm)
Depth	11.5 inches (29.2 cm)	17.12 inches (43.5 cm)
Weight	13.88 lbs (6.30kg)	25.70 lbs (11.70kg)

OPERATING ENVIRONMENT

Operating Temp.	41°F to 95°F (5°C to 35°C)	41°F to 95°F (5°C to 35°C)
Power Supply	240W - 100VAC to 240VAC / 50HZ to 60HZ	290W - 100VAC to 240VAC / 50HZ to 60HZ
Relative Humidity		
Operating:	20% to 80% non-condensing	20% to 80% non-condensing
Storage:	5% to 95% non-condensing	5% to 95% non-condensing
BTU	819 BTU/HR	990 BTU/HR

WARRANTY

3 And 5 year (basic, NDB, or 4HR)

Company and product names mentioned are registered trademarks of their respective owners. Salient Systems reserves the right to change specifications without prior notice. Copyright Salient Systems. 4/2017

