



AR-UPSMON AlphaRefuge™ Uninterruptable Power Supply Monitor



AR-UPSMON ALPHAREFUGE™ UNINTERRUPTABLE POWER SUPPLY MONITOR

The AR-UPSMON AlphaRefuge™ Uninterruptable Power Supply Monitor monitors the PWRAPC or PWRAPC116 power supply. If the system loses 120VAC power and switches to the UPS back-up, it will provide an alarm contact closure, which connects to the customer's fire alarm system, for supervision alarm purposes.

SPECIFICATIONS

- Dimensions: 3.125" W x 5.25" H x 2.63" D (80mm x 134mm x 67mm)
- POLARIZED COIL INPUT(S): DC control inputs only
- ENERGIZED INDICATOR: One red LED per module position
- CONTACT CONSTRUCTION: Dry form "C" DPDT per module position
- CONTACT RATINGS: Resistive load: 7A @ 30vdc, 10A @ 125vac, 7A @ 250vac Inductive load: .25 HP 125/250vac (N.C.), .33HP 125/250vac (N.O.)
- AMBIENT TEMPERATURE: 32°F to 120°F (0°C to 49°C) @ 93% RH (@32°C) Non-Condensing / Non-Freezing
- WIRING: Solid or stranded: #14 to #22 AWG terminals

Alpha Communications

42 Central Drive • Farmingdale • NY • 11735-1202 • Phone: (631) 777-5500 • Fax: (631) 777-5599
TOLL-FREE: (800) 666-4800 • Web: www.alphacommunications.com • Email: info@alphacommunications.com

Copyright© 1998-2021 Alpha Communications® - All Rights Reserved.

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.