HW-TG7FS-A/HW-TGFS-V

CLSS-Enabled 5G /LTE-M Commercial Fire Alarm Communicators for AT&T® and Verizon®

The dialer capture solution to connect commercial fire systems to central monitoring stations and the CLSS Cloud.

Enabled by cooperation between Telguard® and Honeywell®, the HW-TG7 Fire Series starts with Telguard's model TG-7FS and adds the powerful capabilities of Honeywell's Connected Life Safety Services (CLSS) Cloud.

Operating on LTE-M networks, for 5G longevity, lower power consumption, better inbuilding penetration, and compliant with 2019 and earlier editions of NFPA 72, the CLSS LTE-M Fire Communicator can serve as the sole communication path. For existing installations, all landlines dedicated to the master control unit can be replaced with a single CLSS LTE -M Fire Communicator because of its 5 or 60-minute supervision modes.

HONEYWELL CONNECTED LIFE SAFETY SERVICES (CLSS)

Honeywell CLSS is an innovative, all-in-one cloud platform that enables systems integrators and facilities managers to deliver an enhanced fire safety service, while maximizing the performance efficiencies offered by Honeywell's trusted detection and alarm systems. The CLSS platform enables users to:

- Get a "bird's eye" view of all accounts
- · Obtain real-time information on event generation, enabling diagnosis before dispatch
- Conduct tests and inspections using a mobile app (available in select markets)
- Provide end users with multi-site asset information and event alerts

TELGUARD INTERNET PORTAL

Telguard makes adopting cellular easy with a secure internet portal that provides total account management of UL-listed Telguard cellular alarm communicators. Quickly access Telguard-based services 24/7.

TELGUARD CELLULAR SERVICE

Telguard Cellular Service provides AT&T and Verizon® 5G/LTE-M network coverage for all Telguard units. In Canada, cellular service may be provided by Rogers™, Bell®, TELUS®, or SaskTel™. Telguard's Communication Center is UL compliant and provides seamless SaskTel. Telguard's Communication Center is UL compliant and provides seamless station. Telguard technical support provides a single point of contact for both cellular service and Telguard product questions.



TURBOCHARGED BY HONEYWELL FORGE®

A powerful software platform that enables Honeywell to provide realtime data and intelligence in its applications for connected buildings.

FEATURES AND BENEFITS

- Integration with CLSS enables
 monitoring of event transmission data &
 management of device inventory from the
 CLSS mobile app and web portal (available
 only when using Contact ID and pointbased reporting)
- Alarm format support for contact ID, SIA2pulse (3x1, 4x2), modem lle, IIIa, and DMP
- Certified for use on the AT&T and Verizon LTE networks
- Meets UL 864 requirements for sole primary or backup path communications

- Minimizes false alarms by providing dual paths for self-tests
- Falls back to 3G/4G if an LTE network is not available, for extended network coverage
- 60- or 5-minute cellular supervision available; 180-seconds available in Canada
- Telephone line monitor built-in, with standard line security
- Automatic self-test (daily or 6-hour)
- Available relay output for tripping the alarm control panel when a trouble condition occurs
- Locking, red metal enclosure

- Two programmable supervisory trip outputs
- Allows full data reporting for unlimited point-to-point signal details and maximum transmitting power for superior in-building penetration





HW-TG7FS-A/HW-TGFS-V TECHNICAL SPECIFICATIONS

ELECTRICAL

Power Consumption, Standby:

- 18mA @ 24VDC
- 40mA @ 12VDC

Transmit:

- 110mA @ 24VDC
- 20mA @ 12VDC

PHYSICAL

- **Dimensions:** 7.5" (190.5 mm) H x 11.5" (292 mm) W x 3.5" (89 mm) D
- Shipping Weight: 6.5 lbs / 2.95 kg
- Operating Environment: 32°F (0°C) to 122°F (50°C); up to 95% humidity (noncondensing)

RADIO TRANSCEIVER

- Transmit Power: 200 mW in all bands
- LTE Bands: 2.4 & 17
- 3G Bands: 2 & 5
- Antenna: 9" dipole with 2dBi gain 12 ft of cable and universal mounting bracket
- FCC: Part 15, 22, 24, 27 and 68 compliant

ORDERING INFORMATION

HW-TG7FS-A: CLSS 5G/LTE-M Fire Communicator for AT&T

HW-TG7FS-V: CLSS 5G/LTE-M Fire

Communicator for Verizon

Accessories Available from Telguard:

- Low Loss, High Performance Cables:
 - **-ACD-12:** 12 ft (3.7m)
 - -ACD-35: 35 ft (10.7m)
 - **-ACD-50:** 50 ft (15.2m)
 - -ACD-100: 100 ft (30.5m)
- HGDL-0: High Gain Directional LTE

- EXDL-0: External Omnidirectional LTF **Antenna**
- TP-PEM: Power & Expansion Module (supports 24V aux power from FACP toTG-7FS and multiple inputs)

STANDARDS AND CODES

UL Listings:

- 864: Control units and accessories for fire alarm systems
- 365: Police Station connected burglar alarm units and systems
- 1610: Central station burglar alarm units; Line security services
- **\$304:** Canadian commercial burglary alarm systems
- S559: Equipment for fire signal receiving centres and systems

*In Canada, cellular data may be carried by Rogers, Bell, TELUS, or SaskTel.

Visit www.telguard.com for the most current product listings.

AT&T® is a registered trademark of the AT&T Properties, L.P.

Bell® is a registered trademark of Bell Canada.

Honeywell® and HONEYWELL FORGE® are registered trademarks of Honeyell International, Inc.

Rogers[™] is a trademark of Rogers Communications Inc.

SaskTel™ is a trademark of Sasktel.


Telguard[®] is a registered trademark of the Telular Corporation, a bussiness unit of AMETEK. Inc.

TELUS® is a registered trademark of the TELUS Corporation.

Verizon® is a registered trademarkof Verizon Trademark Services LLC.

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

Country of origin: U.S.A.



Honeywell International, Inc.

www.fire.honeywell.com

Telguard



