WI-FI 6

eero 6+

Supports speeds up to a gigabit

- Dual-band mesh Wi-Fi 6 router capable of supporting speeds up to a gigabit
- eero 6+ supports additional wifi bandwidth on the 160 MHz radio channel, so customers have enough wifi to work, stream, and video chat



TOP PRODUCT BENEFITS



Supports 75+ devices with up to 1,500 sq. ft. of coverage per device



The eero app guides you through setup and allows you to manage your network from anywhere



Works as a smart home hub so you can control supported Thread and Zigbee devices with Alexa



Patented TrueMesh technology intelligently routes traffic to reduce drop-offs and eliminate dead spots



Receive automatic updates to help keep your network safe and secure—online security and additional network management features available via a separate subscription



With cross-compatible hardware, you can easily add eero products as your needs change

SKU NUMBERS

PACKAGING INCLUDES

1pk: R011111

Power adapter and Ethernet cable

TECHNICAL SPECIFICATIONS

Wifi

Wifi standards

Wi-Fi 6 (IEEE802.11a/b/g/n/ac/ax)

Number of radios

2; dual-band

eero PoE adapter compatible?

No

MiMO

2x2/2x2

Spatial streams

4

Channel width 20, 40, 80, 160 MHz

Network Security and Services Profiles, WPA3 (eero Labs feature), WPA2, TLS v1.2+, VPN passthrough, IPv6, NAT, UPnP,

port forwarding, DHCP, static IP, and cloud connectivity

connectivity

Other wifi features WMM, Tx Beamforming, OFDMA

AC rating

AX3000

Channel selection

Automatic Channel Selection

Band steering

Yes

Optimize for conferencing and gaming

Yes (eero Labs feature)

Warranty and support

1-year limited warranty

FCC ID

2AEM4-41123474

Parental Controls

Device/profile pause

Yes

Easy password sharing for guest and

home network

Yes

Smart Home Connectivity

Zigbee Smart Home Hub

Yes

Thread Border Router Support

Yes

Bluetooth

Bluetooth Low Energy 5.0

Zigbee

Yes

Works with Alexa

Yes

Radio Frequency

Antenna

2.4 GHz: 2x2 5 GHz: 2x2

Frequency bands

ISM (2.4-2.484 GHz) U-NII-1 (5.15-5.25 GHz) U-NII-2A (5.25-5.35 GHz, DFS)

U-NII-2C (5.47-5.725 GHz, DFS) U-NII-3 (5.725-5.85 GHz)

U-NII-4 (ch 169, 173, 177) **Types of modulation**

OFDM

Physical Interface

Ethernet

 2×1 auto-sensing Gigabit ports, RJ-45

Performance and Capacity

Peak PHY rates

2.4 GHz: 574 Mbps 5 GHz: 2402 Mbps

Processor

1 GHz dual-core processor

Memory

512 MB RAM

Storage

4 GB flash storage

Physical Characteristics

Actual size and weight may vary by manufacturing process

Size

3.90 in x 3.80 in x 2.60 in (99.4 mm x 97 mm x 65.9 mm)

Weight

315 g

Operating temperature

32°F-104°F (0°C-40°C)

Power Requirements

Electrical requirement

100-240V AC, 50-60 Hz

Power supply

15W external

Management Tool

End user

iOS/Android App

Service provider

Remote Network Management

Works With Alexa not available in all countries. Some features require linking your Amazon account, and downloading the Alexa application or using a compatible Alexa device. Internet connection speeds and availability depend on your internet service provider; if your internet service provider; if your internet service provider does not provide you with the maximum supported speed, you will not experience that maximum speed. Maximum miveless signal released and very when connected to an eero device that is configured as a wireless extender. Rowards when connected an eero device that is configured as a wireless extender. Coverage estimates are based on normal use conditions. Actual range and performance can vary, and maximum supported speeds may not be available to all customers, due to factors such as local regulations (including power limits), network configuration, interference, connected devices, device usage, building materials, and obstructions. Specifications are based on use of a Wi-Fi 6 or later generation client device that supports 160 MHz. For more information about eero performance, visit support.eero.com.