



4MP QUAD HD & 4K ULTRA HD CAMERAS

FLIR QUASAR™ PREMIUM BULLET

FLIR designed the Quasar Premium Bullet for vigilant situational awareness in the most demanding environments and for capturing critical evidential and forensic video.

Available in 4MP QHD or 4K UHD, Quasar Premium Bullet cameras deliver superior image quality and IR-illumination for exceptional performance. They're ideal for critical infrastructure sites, remote facilities, or any large areas requiring close monitoring.

Quasar premium cameras are fully NDAA-compliant, come equipped with high-end cybersecurity safeguards, and use low bandwidth. Compatibility with the FLIR eco-system of accessories as well as the ability to operate more cameras on the same network both contribute to a lower total cost of ownership. Seamless integration with a wide range of video management systems, including United VMS provides an open, true end-to-end solution.



BUILT FOR HARSH ENVIRONMENTS

Rugged design, greater operational efficiencies, and fast setup

- IK10 vandal protected for prison, transport, city surveillance, and public access facilities.
- IP67 environmental protection with extreme operating temperature range from -40C to 60C & cold start -40C
- Works in no light conditions with on-board IR-illumination up to 60m
- Suitable for port and other marine environments with salt tolerance



VERSATILE, INTUITIVE, SECURE

Install and set up camera with United VMS within minutes and minimize implementation costs

- Reduce system complexity with easy set-up and control via United VMS and other third-party VMS (ONVIF conformant and cyber-certified)
- Record on the edge with on-board 512GB SD-card, while adding redundancy to the system
- Password protection and policy enforcement, IP address filtering, HTTPS encryption, IEEE 802.1X network access control, digest authentication, CA & self-signed certificates



SUPERIOR IMAGE QUALITY

Optimal resolution and adaptive streaming during surveillance and forensic reporting

- Low light sensitivity requiring only 0.07 lux to produce a color picture
- 3 shutter Wide Dynamic Range (130dB) provides optimal light balance
- Powerful encoding for extra number of streams and FPS customization
- Supports wide 1G network for better streaming and no bandwidth issues

| Camera | Quasar 4K | Quasar QHD |
|------------------------------------|--|---|
| Image Sensor | 1/1.8" CMOS | 1/2.8" CMOS |
| Sensor Resolution | 3840 x 2160 | 2560 x 1440 |
| Scanning Mode | Progressive | |
| Lens Type | CB-6408-11-I: Varifocal 3.6-10mm, 97°-46° HFOV, F1.5, D/N, motorized auto-focus / auto-iris, P-Iris lens CB-6408-21-I: Varifocal 9-22mm, 62°-26° HFOV, F1.6, D/N, motorized auto-focus / auto-iris, P-Iris lens | CB-6404-11-I: Varifocal 2.7-13.5mm, 102°-32° HFOV, F1.4, D/N, motorized auto-focus / auto-iris, P-Iris lens CB-6404-21-I: Varifocal 9-22mm, 39°-16.5° HFOV, F1.6, D/N, motorized auto-focus / auto-iris, P-Iris lens |
| Automatic Electronic Shutter (AES) | 1/2-1/32000 (auto) | |
| Digital Slow Shutter (DSS) | 1/2-1/30(NTSC) 1/2-1/25(PAL) | |
| White Balance | Auto / ATW / Manual / One Push | |
| Automatic Gain Control (AGC) | Auto | |
| Back Light Compensation | On / Off | |
| Shutter WDR | 130dB on 15 FPS 120dB on 30 FPS | |
| Noise Reduction | 3D & 2D | |
| Tamper Detection | Yes | |
| Privacy Zones | Yes | |
| Video Motion Detection | Yes | |
| Day / Night Mode | Yes, support for Enhanced Low Light performance | |
| Mechanical IR Cut Filter | Yes | |
| Signal to Noise Ratio (SNR) | ±50 dB | |
| Sensitivity | 0.07 (color)/0.01 (BW), 0 Lux with IR illuminator ON, measured at 30 IRE | |
| Video | | |
| Compression | Enhanced H.265 Main Profile + Enhanced H.264 Main/High/Baseline Profile + MJPEG | |
| Maximum Performance | H.264/H.265 30/25 FPS @ 4K + H.264/H.265 30/25 FPS @ 1080p (NTSC/PAL) | H.264/H.265 30/25 FPS @ 1440P + H.264/H.265 30FPS @ 1080p MJPEG 15FPS @ 1080P + H.264/H.265/MJPEG 30FPS @ 720P (NTSC/PAL) |
| Resolution Range | Scalable from D1 to 4K | Scalable from D1 to Quad HD 2560 x 1440 |
| Rate Control | CBR, CVBR, MJPEG | |
| SD Card Recording ¹ | MicroSDXC up to 512GB, SD Bus Mode UHS I | |
| IR Illuminator | | |
| Distance | CM-640X-11-I: 40m (131 ft.) CM-640X-21-I: 60m (197 ft.) | |
| Angle of Illumination | CM-640X-11-I: 90° CM-640X-21-I: 60° | |
| LED Type | High efficiency SMD | |
| Peak Emission Wavelength (nm) | 850 | |
| Network | | |
| Network Protocols | IPv4, IPv6, HTTP, HTTPS, UPnP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, ICMP, IGMP, DHCP, ARP, IEEE 802.1X, FTP, RTCP, PPPoE, SMTP, SNMP, QoS, TLS, LDAP, ONVIF Profile G / T / S | |
| Ethernet | 10/100,1000 IEEE 802.3, auto sensing 1 x RJ45 | |
| Remote Configuration | Via web browser or supported video management software | |
| Firmware Upgrade | Flash memory for upgrade of camera firmware over the network | |
| Supported Web Browser | Internet Explorer, Firefox, Chrome, Edge, Opera | |
| Security | Password protection, Password policy enforcement, IP address filtering, HTTPS encryption, IEEE 802.1X network access control, Digest authentication, CA & self-signed certificates Protect from failed log-in Service Firewall | |

¹ SD card not included

| Camera | Quasar 4K | Quasar QHD |
|----------------------------------|--|--------------|
| Audio | | |
| Bi-Directional Audio | 1 Audio Line Input, G.711 a/μ-law, AAC support + 1 Audio Line Output | |
| Alarm | | |
| Input | 1 dry alarm contact | |
| Output | 1 Relay Contact | |
| Physical | | |
| Enclosure | Indoor/Outdoor: IK10 rated vandal IP67 | |
| Dimensions | 258.41x92.76x92.47mm (10.17x3.65x3.64 in.) | |
| Unit Weight | 1.086kg (2.39 lbs.) | |
| Mechanical | | |
| Pan / Tilt / Spin | 360° / ±90° / 360° | |
| Electrical | | |
| Input Voltage | AC24V, DC12V, POE+ | |
| Power Consumption | With Heater and IR DC 12V / 18W AC 24V / 17.64W POE / 17W | |
| Power Connector | PoE - RJ45 DC 12V / AC 24V - Terminal block | |
| Environmental | | |
| Operating Temperature | -40°C to 60°C (-40°F to 140°F) cold start | |
| Storage Temperature | -40°C to 60°C (-40°F to 140°F) | |
| Humidity | 0% - 95% | |
| Shock & Vibe | ISTA 2A | |
| Defog | Yes. Heater ring | |
| Salt Tolerant | NEMA 4X | |
| Warranty & Regulatory | | |
| Warranty | According to FLIR RMA Policy and Process Notice document | |
| USA | UL, FCC Part 15 (subpart B, class A) | |
| International | CE marked, EN61000-6-3 & EN50130-4, RoHS, RCM, WEEE | |
| MTBF | 317988 hours | 310104 hours |

CORPORATE HEADQUARTERS
FLIR Systems, Inc.
1201 S. Joyce Street
Suite C006
Arlington, VA 22202
USA
PH: +1 703.682.3400

FLIR SECURITY HEAD OFFICE
FLIR Systems, Inc.
6769 Hollister Ave.
Goleta, CA 93117
USA
PH: +1 805.690.6600

www.flir.com
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2021 FLIR Systems, Inc. All rights reserved. Rev. 02/04/21

20-1576-SEC-Bullet



The World's Sixth Sense®