

Rack PDU, Switched, 1U, 16A, 208/230V, (8)C13

AP7921B

			W

Presentation This APC Switched Rack PDU power distribution unit has a wide range of standardized PDU features that increase network efficiency, manageability and functionality. The output and input connections are (8)C13. Network management capabilities allow you to configure and manage rack PDUs from remote locations. It has has a local current monitoring display that gives a visible warning in case of an overload. The remote individual outlet control provides real-time monitoring of connected loads. It has a multi-tier user access that enables you to restrict unauthorized use of outlets. This rack has a single input power source making it easy to install.

Lead time Usually in Stock

Main	
Main Input Voltage	200 V 208 V 230 V
Main Output Voltage	208 V 230 V
Plug standard	IEC 60320 C20
Number of rack unit	1U
Cable length	2.50 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets User manual

Physical

Colour	Black
Height	4.4 cm
Width	44.5 cm
Depth	10.8 cm
Net weight	2.27 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

[In] rated current	16 A

Permissible voltage	200240 V
Input current limits	20 A
Load capacity	3680 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets 8 IEC 60320 C13

Conformance

Product certifications	cUL listed CE CSA GOST IRAM MIC UL listed VDE
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 UL 60950

Environmental

Ambient air temperature for operation	045 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	095 %
Storage altitude	0.0015240.00 m

Packing Units

Package 1 Weight	3.45 kg
Package 1 Height	7 cm
Package 1 width	47 cm
Package 1 Length	34.3 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty

2 years repair or replace