

# Product data sheet

Specifications



## APC Rack PDU, 2G, switched, 0U, 30A, 100V to 120V, 24 NEMA 5-20R sockets

AP8932

### Overview

Presentation	APC Switched Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and active monitoring. Remote outlet level controls allow power on/off functionality for power recycling to remotely reboot equipment and restrict unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and low profile circuit breakers. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched Rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.
--------------	---

Lead time	Usually in Stock
-----------	------------------

### Main

Main Input Voltage	100 V 120 V
Main Output Voltage	100 V 120 V
Plug standard	NEMA L5-30P
Number of rack unit	0U
Cable length	3.00 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets Serial configuration cable Safety guide

### Physical

Colour	Black
Height	179.1 cm
Width	5.5 cm
Depth	4.6 cm
Net weight	7.85 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

[In] rated current	24 A
Permissible voltage	100...120 V
Input current limits	30 A
Load capacity	2880 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets	24 NEMA 5-20R
--------------------------------	---------------

Conformance

Product certifications	cUL listed PSE UL listed
Standards	FCC part 15 class A ICES-003 UL 60950-1

Environmental

Ambient air temperature for operation	-5...60 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Package 1 Weight	9.66 kg
Package 1 Height	200.6 cm
Package 1 width	16.47 cm
Package 1 Length	10.83 cm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Lead free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------