

# Product data sheet

Specifications



## APC Rack PDU, 9000 switched, 0U, 30A, 200V and 208V, 21 C13 and C15, 3 C19 and C21 sockets

APDU9941

### Overview

|           |                  |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

### Main

|                             |  |
|-----------------------------|--|
| Main Input Voltage          | 208 V<br>200 V   |
| Main Output Voltage         | 200 V<br>208 V   |
| Plug standard               | NEMA L6-30P  |
| Number of rack unit         | 0U   |
| Cable length                | 3.05 m   |
| Number of cables            | 1  |
| Communication port protocol | SNMP<br>Redfish  |
| Provided equipment          | Installation guide<br>Rack mounting brackets<br>Safety guide |

### Physical

|                     |                    |
|---------------------|--------------------|
| Colour              | Black              |
| Height              | 182.9 cm           |
| Width               | 5.5 cm             |
| Depth               | 4.6 cm             |
| Net weight          | 8.5 kg             |
| Mounting location   | Side               |
| Mounting preference | No preference      |
| Mounting mode       | Not rack-mountable |
| USB compatible      | No                 |

### Input

|                      |         |
|----------------------|---------|
| [In] rated current   | 24 A    |
| Max line current     | 30 A    |
| Input current limits | 30 A    |
| Load capacity        | 4992 VA |

|                   |          |
|-------------------|----------|
| Network frequency | 50/60 Hz |
|-------------------|----------|

## Output

|                                |                         |
|--------------------------------|-------------------------|
| Number of power socket outlets | 21 C13/C15<br>3 C19/C21 |
|--------------------------------|-------------------------|

## Conformance

|                        |  |
|------------------------|--|
| Product certifications | cUL listed<br>FCC part 15 class A<br>PSE |
| Standards              | ICES-003                                 |

## Environmental

|                                       |                   |
|---------------------------------------|-------------------|
| Ambient air temperature for operation | -5...60 °C        |
| Relative humidity                     | 5...95 %          |
| Operating altitude                    | 0...10000 ft      |
| Ambient air temperature for storage   | -25...65 °C       |
| Storage Relative Humidity             | 5...95 %          |
| Storage altitude                      | 0.00...15240.00 m |

## Batteries & Runtime

|                            |                   |
|----------------------------|-------------------|
| Communication network type | 10/100/1000BASE-T |
|----------------------------|-------------------|

## Packing Units

|                              |         |
|------------------------------|---------|
| Package 1 Weight             | 10 kg   |
| Package 1 Height             | 204 cm  |
| Package 1 width              | 16.5 cm |
| Package 1 Length             | 12.4 cm |
| Number of Units in Package 3 | 48      |

## Contractual warranty

|          |                           |
|----------|---------------------------|
| Warranty | 3 years repair or replace |
|----------|---------------------------|