













FUNCTIONS

- 5MP (2592 x 1944)
- Motorized Varifocal 2.7-13.5mm Lens
- HD-TVI / CVI / AHD / CVBS (Analog)
- Easy-to-Use DIP Switch to Change Formats
- True Day / Night
- Smart IR Illumination Up to 115ft.
- Digital NR
- DWDR
- IP67 Outdoor Rating
- DC 12V (5W Consumption)


5MP HD-TVI VARIFOCAL TURRET CAMERA


5MP HD-TVI VARIFOCAL TURRET CAMERA WITH HD OVER COAX FEATURES

Our Second Generation HD-TVI Series continues providing the quality expected from the AVYCON brand. This 5MP camera includes an upgraded Smart IR LED array, new DIP switch design for easily changing video formats (HD-TVI, CVI, AHD and Analog), and a sleek new magnetic ring designed to hide all mounting screws from view and create a seamless body look. With the newest generation chipset and board design, we have also increased power efficiency with a possible 20% savings in consumption. This camera also includes a motorized 2.7mm-13.5mm Varifocal Lens with Autofocus capabilities that can be controlled through the DVR. Also standard with this series is Digital NR, AGC, DWDR, and BLC capabilities along with IP67 outdoor rating.

DIMENSIONS

Unit: inch (mm)





OPTIONAL ACCESSORIES



AVM-JB-BE-S1 JUNCTION BOX



AVM-CWM-EV-S1



AVM-HWM-E-S1



AVM-HCM-E-L1 CEILING MOUNT



AVM-CRM-A1
CORNER MOUNT



POLE MOUNT

SPECIFICATIONS

CAMERA	
Image Sensor	1/2.7" Progressive Scan CMOS
Resolution	5MP
Image Size	2592 x 1944
Video Output	1-channel BNC Video Output
Image System	
Electronic Shutter	1/15s to 1/50,000s
	Up to 115ft.
Video Formats	HD-TVI / AHD / CVI / CVBS (Analog)
	HD-TVI / AHD / CVI / CVBS (Analog): 20 FPS
	CVBS Analog: 30 FPS
Min. Illumination	0.05lux@F1.2(AGC ON),0Lux with IR ON
	Motorized 2.7-13.5mm Lens
Lens Mount	φ14mm
S/N Ratio	40dB
Function Control	OSD, Control over Coax (UTC)
IMAGE	
Day & Night	EXT / Auto / Color / BW (Black and White)
Digital WDR	
Digital NR	Yes (3D DNR)
Auto Gain Control (AGC)	
Auto White Balance (AWB)	Yes
Backlight Compensation (BLC)	
Edge Brightness Compensation	Yes
Defog	No
HLČ	No
Sharpness	Yes
Mirror Image	Yes
Smart IR (Anti-SAT)	Yes
Image Setting	Yes
Defect Correction	Auto / Manual
Language	Support for 12 Different Languages
GENERAL	
Angle Adjustment	Any Angle
	DC 12V (±10%)
Power Consumption	
Ingress Protection	
	-22F - 131F (-30°~55° Celcius)
Dimensions	4.96" x 3.15" (126.0mm x 80.0mm)

Copyright © AVYCON. All rights reserved. Specifications and pricing are subject to change without notice.

phone: 949-752-7606 email: info@avycon.com social: @avycon_aivo website: avycon.com