













FUNCTIONS

- 8MP (3840 x 2160)
- Motorized Varifocal 2.7-13.5mm Lens
- HD-TVI / CVI / AHD / CVBS (Analog)
- Easy-to-Use DIP Switch to Change Formats
- True Day / Night
- Smart IR Illumination Up to 115ft.
- Digital NR
- DWDR
- IP67 Outdoor Rating
- DC 12V (6W Consumption)


8MP HD-TVI VARIFOCAL TURRET CAMERA


8MP HD-TVI VARIFOCAL TURRET CAMERA WITH HD OVER COAX FEATURES

Our Second Generation HD-TVI Series continues providing the quality expected from the AVYCON brand. This 4K camera includes an upgraded Smart IR LED array, new DIP switch design for easily changing video formats (HD-TVI, CVI, AHD and Analog), and a sleek new magnetic ring designed to hide all mounting screws from view and create a seamless body look. With the newest generation chipset and board design, we have also increased power efficiency with a possible 20% savings in consumption. This camera also includes a motorized 2.7mm-13.5mm Varifocal Lens with Autofocus capabilities that can be controlled through the DVR. Also standard with this series is Digital NR, AGC, DWDR, and BLC capabilities along with IP67 outdoor rating.

DIMENSIONS

Unit: inch (mm)





OPTIONAL ACCESSORIES



AVM-JB-BE-S1 JUNCTION BOX



AVM-CWM-EV-S1
COMPACT WALL MOUNT



AVM-HWM-E-S1 HEAVY-DUTY WALL MOUNT



AVM-HCM-E-L1 CEILING MOUNT



AVM-CRM-A1



POLE MOUNT

SPECIFICATIONS

CAMERA	
Image Sensor	1/2.7" Progressive Scan CMOS
Resolution	8MP
Image Size	3840 x 2160
	1-channel BNC Video Output
Image System	
	1/15s to 1/50,000s
	Up to 115ft.
	HD-TVI / AHD / CVI / CVBS (Analog)
	HD-TVI / AHD / CVI / CVBS (Analog): 15 FPS
	CVBS Analog: 30 FPS
Min. Illumination	0.05lux@F1.2(AGC ON),0Lux with IR ON
	Motorized 2.7-13.5mm Lens
Lens Mount	
S/N Ratio	
	OSD, Control over Coax (UTC)
IMAGE	
Day & Night	EXT / Auto / Color / BW (Black and White)
Digital WDR	
	Yes (3D DNR)
Auto Gain Control (AGC)	
Auto White Balance (AWB)	
Backlight Compensation (BLC)	
Edge Brightness Compensation	Yes
Defog	
HLČ	No.
Sharpness	
Mirror Image	
Smart IR (Anti-SAT)	
Image Setting	
Defect Correction	Auto / Manual
Language	Support for 12 Different Languages
GENERAL	
Angle Adjustment	Any Angle
Input Voltage	DC 12V (±10%)
Power Consumption	
Ingress Protection	
Working Environment	-22F - 131F (-30°~55° Celcius)
Dimensions	4.96" x 3.15" (126.0mm x 80.0mm)

Copyright © AVYCON. All rights reserved. Specifications and pricing are subject to change without notice.

phone: 949-752-7606 email: info@avycon.com social: @avycon_aivo website: avycon.com