



FG-730

Glassbreak Detector

The Honeywell Home FlexGuard® FG-730 incorporates the most reliable, field-proven technology available – setting the industry standard in glassbreak detectors.



FEATURES AND BENEFITS

- **Field Proven Design**
The world's best selling glassbreak detector.
- **Dual Technology Flex-Audio Principle**
Positively detects and confirms breaking glass by analyzing both "flex" (impact) and "audio" (shattering) frequencies. For an alarm to occur the flex signal must be followed by an audio signal within a prescribed time frame.
- **Signal Verification**
Both flex and audio signals must register valid amplitude, duration and frequency for an alarm to occur.
- **Signal Filtering**
Thorough filtering and processing of all signals provides greater immunity to false alarms.
- **Broad Range**
Detects glass breakage from distances up to 30' (9m). The FlexGuard FG-730 detector sets the industry standard in glassbreak detectors.
- **Dual Flex/Audio Technology**
Provides excellent catch performance while virtually eliminating false alarms.
- **Indicator LEDs**
LED alarm indicator for testing flex and audio technologies.
- **Burst Rejection Circuit**
Ignores short flex/audio noise burst signals present in some environments.
- **Circuit Protection**
Prevents shorts, overloads and reverse-polarity connections from causing damage.
- **Alarm Memory**
Alarm LED can be set to latch upon alarm; helps identify which unit alarmed in multiple detector applications.
- **RFI Immunity**
100 watts at 3m (10') from all mobile bands 27–1000 MHz.
- **Easy Installation and Set-Up**
Mount within 9m (30') of the glass to be protected. (Can be adjusted to suit characteristics of each location.)
- **Low Voltage Operation**
10–14VDC
- **Low Current Draw**
25mA at 12VDC

FG-730 Technical Specifications

Physical Dimensions: White, high impact, ABS plastic housing; 10cm H x 6.2cm W x 2cm D (3-7/8" x 2-2/5" x 4/5")

Weight: 85 g (3 oz)

Range: 9 m (30')

Mounting Locations: Ceiling, opposite wall, adjoining wall, same wall as glass

Alarm Relay: Form C, 500mA max, 30VDC max

Tamper Switch:

Form A (NC) 50mA, 30VDC

Power Requirements: 10–14VDC 25mA at 12VDC

Operating Temperature: 0°–49° C (32°–120° F)

Set-Up Tester: FG-701 Glassbreak Simulator Also works with FG-700 Glassbreak Simulator

Approvals and Listings: UL Listed

Glass Type/Thickness: Minimum size for all glass types is 11" x 11" (28cm x 28cm) square; glass must be framed in the wall of the room or mounted in a barrier of 36" (.9m) minimum width.

| TYPE* | MINIMUM | MAXIMUM |
|------------|---------------|----------------|
| Plate | 2.4mm (3/32") | 6.4mm (1/4") |
| Tempered | 3.2mm (1/8") | 6.4mm (1/4") |
| Laminated* | 3.2mm (1/8") | 14.3mm (9/16") |
| Wired | 6.4mm (1/4") | 6.4mm (1/4") |
| Coated** | .2mm (1/8") | 6.4mm (1/4") |
| Sealed | 3.2mm (1/8") | 6.4mm (1/4") |

* Laminated and sealed insulating glass types are protected only if both plates of glass are broken.

** For glass coated on the inner surface with 3M Scotchtint™ type RE35NEARL or Hardglass Security Film, reduce maximum effective range to 15' (4.6m).

ORDERING

| | |
|--------|-----------------------------|
| FG-730 | Glassbreak Detector |
| FG-701 | Glassbreak Simulator/Tester |

For more information

security.honeywellhome.com/hsc



Resideo Technologies, Inc.

2 Corporate Center Drive, Suite 100
P.O. Box 9040
Melville, NY 11747
1-800-645-7492
resideo.com

L/FG730/D | 06/19
© 2019 Resideo Technologies, Inc.
This product is manufactured by Resideo and its affiliates. The Honeywell Home trademark is used under license from Honeywell International Inc. All rights reserved.

Honeywell Home