

Keyscan K-PROX3

proximity reader



Keyscan K-PROX3 proximity reader

The Keyscan K-PROX3 is a robust and affordable reader with a sleek, modern finish. The K-PROX3 features stellar technology, multiple mounting options, heartbeat intelligence, and anti-tamper capability (optional equipment required) for unrivaled performance and dependability.

K-PROX3 boasts dedicated features designed for exclusive use with Keyscan's Present3 and facility lockdown function. The reader will indicate status with new auxiliary LED indicators. These features are enabled by default (out of the box) and will function with all PC1097 panels with firmware 9.39 (higher). For use with legacy systems (PC 1095) or other manufacturer's systems – these features must be turned off, before use, with the optional K-PC1 programming card.

The K-PROX3 is the ideal choice for Keyscan access control systems with 125 kHz proximity reader requirements.

- Provides an innovative 'heartbeat' technology. If this heartbeat is interrupted due to wiring fault or damage an alarm condition is triggered by the Keyscan control panel when enhanced features are activated
- New dedicated LED indicators for Keyscan Present3 and facility lock down features (requires firmware 9.39 and K-PC1 programming card)
- On board beeper to generate audible tones or sound a local "door-held-open" alert
- Versatile mounting options with 2-in-one, mullion or single gang, electrical box mounting applications
- Epoxy encased electronics are well-suited for both interior or exterior use
- Impressive read range
- Durable, weather-resistant construction for reliable operation and long usage even in harsh environments
- Limited lifetime warranty

Specifications

Size

Mullion: 11.5 cm x 4.49 cm x 1.7 cm (4 7/16" x 1 11/16" x 1 1/16")
Switch Plate: 12 cm x 7.6 cm x 1.6 cm (4 3/4" x 3" x 5/8")

Read Range

Off metal: up to 12.7 cm (5") On Metal: up to 10.2 cm (4")
On Metal: On metal: up to 10.2 cm (4")

*Based upon Clamshell Card

Power Requirements

12 VDC, 80mA

Cable Distance

12" wire pigtail standard
Wiegand interface 500 feet (152 meters)
6 conductor shielded 22 AWG

Operating Temperature

- 40° C to 66° C (- 40° F to 150.8° F)

Installation

Installation and wiring of systems must be in accordance with the National Electrical Code, ANSI/NFPA 70

Connections

Connections must be in accordance with NFPA 70. Reader and/or control unit power sources must not be connected to a receptacle controlled by a switch

Certifications

ANSI/UL 294:1990 Ed:5

CAN/ULC S319-05

FCC + ICC

Canadian industrial design certificate of registration

169, 198 and 169, 199

K-PROX3 dedicated LED features requirements

PC1097 (blue) panels with firmware 9.39 (higher).

For use with PC1095 or all legacy (green) panels

K-PROX3 will only function in basic reader mode.

Dedicated LED features must be turned off before use. Use

K-PC1 programming card (sold separately) to turn features off.

© dormakaba Canada Inc. Control boards require firmware for reader's Present3 and lockdown LEDs. Information on this sheet is intended for general use only. dormakaba reserves the right to alter designs and specifications without notice or obligation. Printed in Canada.

dormakaba Canada
901 Burns St., E.,
Whitby, Ontario
Canada L1N 0E6

1 888 539 7226

www.keyscan.ca

KKT2055 2017-12