



1596B

POWER SUPPLY 33VDC 60W 100-240VAC, PSE CERTIFIED



Power supply unit with 110-230 VAC primary and 33 VDC / 1.8A continuous output for 316 range entrance panels. Equipped with internal protection against current overload and short circuits. Dimensions: 118x92.59x60.5 mm (7 DIN modules). PSE certified.



1596B

POWER SUPPLY 33VDC 60W 100-240VAC, PSE CERTIFIED

MAIN FEATURES

Supply voltage	
Output supply voltage	
Max. current delivered (A)	
Input connector	
Plug-in power supply unit	
Applicable to DIN rail	
Number of DIN modules (n°)	

HARDWARE SPECIFICATIONS

Product weight (oz) (oz)	
--------------------------	--

GENERAL DATA

Height (inch) (pc)	
Width (inch) (pc)	
Depth (inch) (pc)	
Type of finishing materials	
Product color	
Operating temperature (°F) (°F)	

COMPATIBILITY

Simplebus 2 audio/video system	
Building Kit audio/video system	
Simplebus 2 audio system	
Simplebus 1 audio system	
Vip system	
Kit audio/video system	
Ipower system	
Traditional system	
Simplified system	



1596B

POWER SUPPLY 33VDC 60W 100-240VAC, PSE CERTIFIED

COMPATIBILITY

Comelbus system

Comtel system

MOUNTING/INSTALLATION

Wall-mounted

AUDIO/VIDEO FEATURES

Audio system

Audio/video system

CONNECTIVITY

Stabilised output

GENERAL FEATURES

DIN modules (no.) (n°)

DIN rail mounted

Visual signalling