Motion Detectors for all applications



Intrusion detection is a delicate balance between responding to real security breaches and ignoring costly false alarm sources. Our advanced sensors provide best-in-class catch performance while virtually eliminating false triggers such as strong drafts, moving objects, and the presence of pets. Advanced design features ensure an installation that is both faster and more reliable. This reduces the technician's time on the ladder, reduces call-back costs, and lowers the total cost of ownership for your customers.

Wall mount motion detectors

Blue Line Series ISC-BPR2-WP12 ISC-BDL2-W12 ISC-BDL2-WP12 Description ISC-BPR2-W12 ISC-BPQ2-W12 GE/HE GE/HE TriTech TriTech Quad PIR **Type of Motion Detector** PIR PIR (PIR + MW) (PIR + MW) EN50131-2-2/4 grade 2 grade 2 grade 2 grade 2 grade 2 Pet/small animal immunity 4.5kg 4.5kg 4.5kg 45kg **Coverage/Range** 12m x 12m 2.2 to 2.75m 2.2 to 2.75m **Mounting height** 2.2 to 2.75m 2.2 to 2.75m 2.2 to 2.75m Warranty 5 years 8 years 8 years 5 years 5 years **Application** • All Blue Line Series detectors for use in residential and small commercial applications • Use the Quad or the TriTech models for difficult environment

Commercial Series

Commercial Series						
ISC-CDL1-W15	ISC-CDL1-WA15					
GE/HE	GE/HE					

TriTech (PIR+MW)	TriTech+ with Anti-mask (PIR+MW)		
grade 2	grade 3		
4.5kg	4.5kg		
15m x 15m	15m x 15m		
2.3 to 2.75m	2.3 to 2.75m		
8 years	8 years		

- Difficult* environments All Commercial Series detectors for use in small to medium commercial applications
- ISC-CDL1-WA15 also for use in high risk applications

Professional Series

Moli	nting
	ckets

						prackets	
Description	ISC-PPR1-W16	ISC-PDL1-W18 G/H**	ISC-PPR1-WA16 G/H**	ISC-PDL1-WA18 G/H**	ISC-PDL1-WC30 G/H**	ISC-PDL1-WAC30 G/H**	
Type of Motion Detector	PIR	TriTech (PIR+MW)	PIR with Anti-mask	TriTech with Anti-mask (PIR+MW)	TriTech Curtain (PIR+MW)	TriTech Curtain with Anti-mask (PIR+MW)	B328 mounting bracket
EN50131-2-2/4	grade 2	grade 2	grade 3	grade 3	grade 2	grade 3	• B335-3 Swivel- mount bracket
Pet/small animal immunity	4.5kg	4.5kg	4.5kg	4.5kg	4.5kg	4.5kg	B338 Universal ceiling bracket
Coverage/Range	18m x 25m	18m x 25m	16m x 21m	18m x 25m	30m x 2.6m	30m x 2.6m	_
Mounting height	2 to 3m	2 to 3m	2 to 3m	2.1 to 3m	2.1 to 3m	2.1 to 3m	
Warranty	5 years	8 years	8 years	8 years	8 years	8 years	
Application	 Standard environments Medium to high risks 	 Difficult* environments Medium to high risks 	Standard environmentsHigh risks	 Difficult* environments High risks 	 Curtain version Difficult* environments Narrow and long areas Medium to high risk 	 Curtain version Difficult* environments Narrow and long areas High Risk 	 Bosch offers a range of mounting brackets for wall and ceiling mounting for all wall mount detectors The Mounting Brackets listed may be used on Blue Line, Commercial, and Professional Series.

** Currently not available in European Union, Switzerland, Norway and Turkey

Ceiling mount and outdoor detectors

Description	DS936	DS938Z	DS939	DS9370E, DS9371E	OD850
Type of Motion Detector	Panoramic PIR	Panoramic PIR	Panoramic PIR	Panoramic TriTech (PIR + MW)	Outdoor TriTech
EN50131-2-2/4	-	grade 2	grade 2	_	-
Pet/small animal immunity	No	No	No	No	No
Coverage/Range	7.5m and 360°	18m and 360°	21m and 360°	21m and 360°	15m x 15m
Mounting height	2 to 3.6m	2.5 to 6m	2.4 to 7.6m	2.4 to 7.6m	2.3 to 2.75 m
Warranty	5 years	5 years	5 years	8 years	8 years
Application					
	Standard environmentsSmall to medium risksFor residential to small commercial applications	Standard environmentsSmall to medium risksSmall to large commercial applications	Standard environmentsMedium risksSmall to large commercial applications	Difficult* environmentsMedium risksSmall to large commercial applications	 For residential and commercial outdoor applications

- For special room conditions we can recommend one of our ceiling mount detectors:
- Large halls where detectors cannot be mounted on a wall • Large offices with cubicles where wall mount detectors are not possible
- Small convenience stores with small shelves, where field of view is better vertical than horizontal
- We do not recommend ceiling mount detectors where objects are hanging from a ceiling blocking the line-of-sight or where the ceiling is vibrating as in ceiling mounted HVAC units.
- Difficult environments are those which include potential false alarm sources.
- The detector is in the same room as an air conditioning vent
- Strong drafts of cold or warm air in the room
- A fan that could be running when the system is activated
- Detector could be exposed to bright white light
- (car headlights, floodlights, direct sunlight etc.) • Room which contains slow moving objects such as curtains, plants
 - Room has underfloor heating • Room temperature exceeds 30 degrees Celsius