CAST Impressionist® Handheld Dimmer Control (CDIMMER & CDIMMEREW)

CAST Impressionist Series® Light Level Control at the Fixture or Remote Location

Precise 20-step light level control at the fixture.



CDIMMEREW



Construction:

CDIMMER: Sturdy plastic body with 6-foot control cable terminating in 2-pin plug.

CDIMMEREW: 25 ft. cable that extends between the CDIMMER and fixture.

Dimensions: —

 $7'' \log x 2.5'' \text{ wide } x 1.25'' \text{ deep.}$

Care Instructions:

Store in cool dry place. Do not expose to rain or snow. Replace batteries once per year.

Specifications:-

Voltage: 4.0 to 6.7 VDC - (4) AA batteries included.

Current: 0.09 A Max. Power: 0.65 W Max.

Description: -

A primary feature of the ground-breaking CAST Impressionist Series® fixtures is the capability for the designer or end-user to control the light level at the fixture or some remote location. The Handheld Dimmer Control (CDIMMER) is simply plugged into the fixture's control receptacle (located on the fixture lead wire) and the user depresses a button to activate the dimming cycle. Use the optional (CDIMMEREW) for extended length (25ft.) between the CDIMMER and fixture.

Features: _

- 20-step dimming cycle indicated by 10 LED indicator lights on the control unit.
- Dims from 100% to 5%.
- One-button activator initiates the dimming cycle either up or down. Each time the button is depressed the direction reverses.
- Depressing button continuously for 15 seconds bring fixture to full brightness.
- Fixture electronics hold light level in memory.

Controls light levels for all Impressionist Series® fixtures.