



# Lyric™ SiX™

Two-Way Wireless Technology



Designed for the Lyric Controller, Honeywell Home SiX Two-way Wireless Technology delivers significant advantages—including faster installation, easier troubleshooting, remote diagnostics and increased RMR. The suite of next-generation devices include motion, smoke and glassbreak detectors, a door/window sensor, two-way wireless key and siren.



## FEATURES AND BENEFITS

- **Easier to Install**  
SiX sensors feature a battery pull-tab, auto-enrollment and no-touch adjust to speed installation and eliminate errors.  
Devices can be configured remotely as needed, reducing the need to schedule on-site visits.
- **Easier to Maintain**  
The System Health Check feature lets you monitor device signal strength, sensor settings, temperature and battery life anytime, anywhere via AlarmNet 360™, letting you quickly and proactively troubleshoot.
- **Secure Encryption**  
SiX Two-Way Wireless Technology employs true, 128-bit AES encryption for a high level of security.
- **Fewer Truck Rolls**  
Reduce truck rolls with user-replaceable batteries and the ability to remotely adjust sensor parameters and download software updates.
- **Lyric™ Lock**  
When enabled, SiX™ devices are locked into the Lyric panel and must be un-paired by the installing dealer to be used again – helping prevent account takeovers and conversions from competitors.

# Lyric™ SiX™ Technical Specifications



Lyric Door/Window Sensor  
SiXCT

- 
- Mounting Hardware** - Included
  - Transmission Range** - 300 ft (92 meters) plus\*
  - LED Indicators** - Yes
  - Magnetic Gap** - 1.0" (25mm) gap for reed switch
  - Auxiliary Input Terminal** - Yes
  - Temperature Sensing Capable** - Yes
  - Frequency** - 2.4 GHz
  - Encryption** - 128-bit AES
  - Battery Life** - Five years (typical use)
- 

- 
- Power Requirements** - 3 volt CR123 battery (Qty 1)
  - Tamper Protected** - Yes
  - Operating Temperature** - 32°F - 122°F/0°C - 50°C
  - Relative Humidity** - 5-95%, non-condensing
  - Dimensions** - 1.1" H x 1.6" W x 3.1" L/ 28mm H x 41mm W x 79mm L
  - Approval Listings** - FCC/IC, ETL Listed to UL 634, cETL Listed to ULC/ORD-C634
  - Authorized Countries** - US/Canada/Latin America
- 



Lyric Glassbreak Detector  
SiXGB

- 
- Mounting Hardware** - Included
  - Transmission Range** - 300 ft (92 meters) plus\*
  - LED Indicators** - Yes
  - Detection Pattern** - 25 ft (7.6 meters) radius
  - Temperature Sensing Capable** - Yes
  - Frequency** - 2.4 GHz
  - Encryption** - 128-bit AES
  - Battery Life** - Five years (typical use)
- 

- 
- Power Requirements** - 3 volt CR123 battery (Qty 1)
  - Tamper Protected** - Yes
  - Operating Temperature** - 32°F - 122°F/0°C - 50°C
  - Relative Humidity** - 5-95%, non-condensing
  - Dimensions** - 3.7" diameter x 1.1" depth/  
96mm diameter x 29mm depth
  - Approval Listings** - FCC/IC, ETL Listed to UL 639, cETL Listed to ULC-S306
  - Authorized Countries** - US/Canada/Latin America
- 

\*Varies based on each installation due to environmental conditions.

# Lyric™ SiX™ Technical Specifications



## Lyric Two-Way Wireless Key SiXFOB

---

**Mounting Hardware** - Included  
**Transmission Range** - 300 ft (92 meters) plus\*  
**LED Indicators** - Yes  
**Temperature Sensing Capable** - No  
**Frequency** - 2.4 GHz  
**Encryption** - 128-bit AES  
**Battery Life** - Three years (typical use)  
**Power Requirements** - 3 volt 2032 coin cell battery (Qty 1)

---

---

**Tamper Protected** - No  
**Operating Temperature** - 32°F - 122°F/0°C - 50°C  
**Relative Humidity** - 5-95%, non-condensing  
**Dimensions** - 0.4" H x 1.4" W x 2.5" L/  
11mm H x 36mm W x 65mm L  
**Approval Listings** - FCC/IC, ETL Listed to UL 1023  
and UL 985, cETL Listed to ULC/ORD-C1023 and  
ULC-S545  
**Authorized Countries** - US/Canada/Latin America

---



## Lyric Motion Detector SiXPIR

---

**Mounting Hardware** - Included  
**Transmission Range** - 300 ft (92 meters) plus\*  
**LED Indicators** - Yes  
**Detection Pattern** - 40' x 56'  
**Temperature Sensing Capable** - Yes  
**Frequency** - 2.4 GHz  
**Encryption** - 128-bit AES  
**Battery Life** - Five years (typical use)  
**Power Requirements** - 3 volt CR123 battery (Qty 1)

---

---

**Tamper Protected** - Yes  
**Operating Temperature** - 32°F - 122°F/0°C - 50°C  
**Temp. Compensation** - Yes  
**Relative Humidity** - 5-95%, non-condensing  
**Dimensions** - 4.1" H x 2.3" W x 1.5" D/  
105mm H x 60.4mm W x 39.3mm D  
**Approval Listings** - FCC/IC, ETL Listed to UL 639,  
cETL Listed to ULC-S306-03  
**Authorized Countries** - US/Canada/Latin America

---

\*Varies based on each installation due to environmental conditions.

# Lyric™ SiX™ Technical Specifications



Lyric Smoke Detector  
SiXSMOKE

**Mounting Hardware** - Included  
**Transmission Range** - 300 ft (92 meters) plus\*  
**LED Indicators** - Yes  
**Detection Pattern** - 360 degree  
**Temperature Sensing Capable** - Yes  
**Frequency** - 2.4 GHz  
**Encryption** - 128-bit AES

**Power Requirements** - 3 volt CR123 battery (Qty 2)  
**Tamper Protected** - Yes  
**Operating Temperature** - 32°F – 95°F/0°C – 35°C  
**Relative Humidity** - 5-95%, non-condensing  
**Dimensions** - 5.3" diameter x 1.6" depth/  
 135mm diameter x 42mm depth  
**Approval Listings** - FCC/IC, ETL Listed to UL 268 and  
 UL 521, cETL Listed to ULC-S530 and ULC-S531  
**Authorized Countries** - US/Canada/Latin America\*\*



Lyric Siren  
SiXSIREN

**Mounting Hardware** - Included  
**Transmission Range** - 300 ft (92 meters) plus\*  
**LED Indicators** - Yes  
**Detection Pattern** - N/A  
**Temperature Sensing Capable** - Yes  
**Frequency** - 2.4 GHz  
**Encryption** - 128-bit AES  
**Battery Life** - Five years (typical use)  
**Power Requirements** - AA Energizer™ Lithium (Qty 4)

**Tamper Protected** - Yes  
**Operating Temperature** - 32°F - 122°F/0°C - 50°C  
**Relative Humidity** - 5-95%, non-condensing  
**Dimensions** - 5.5" diameter x 1.8" depth/  
 140mm diameter x 46mm depth  
**Approval Listings** - FCC/IC, ETL Listed to UL 985 and  
 UL 1023, cETL Listed to ULC-S545 and, ULC/ORD-C1023  
**Authorized Countries** - US/Canada/Latin America

\*Varies based on each installation due to environmental conditions.  
 \*\*Varies based on part number.

## ORDERING

<b>SIXCT</b>	Lyric Door/Window Sensor	<b>SIXGB</b>	Lyric Glassbreak Detector
<b>SIXPIR</b>	Lyric Motion Detector	<b>SIXFOB</b>	Lyric Two-Way Wireless Key
<b>SIXSMOKE</b>	Lyric Smoke Detector	<b>SIXSIREN</b>	Lyric Siren
<b>SIXSMOKE-CN</b>	Lyric Smoke Detector (Canada)		



**For more information**  
[security.honeywellhome.com/hsc](http://security.honeywellhome.com/hsc)

**Resideo Technologies, Inc.**  
 2 Corporate Center Drive, Suite 100  
 P.O. Box 9040  
 Melville, NY 11747  
 1-800-645-7492  
[resideo.com](http://resideo.com)

L/LYC62WWSD/D | 05/19  
 © 2019 Resideo Technologies, Inc.  
 This product is manufactured  
 by Resideo and its affiliates. The  
 Honeywell Home trademark is  
 used under license from Honeywell  
 International Inc. All rights reserved.

