Single use

UL Listed 711A



Description

The only special purpose fire extinguisher that is UL Listed to 711A (residential cooking equipment)* and meets NFPA 10. The proprietary nozzle design (patent pending) allows a broad, dispersed discharge of agent that delivers a high volume, low velocity delivery of dry chemical.



Includes plastic wall hanger (293633).

At a Glance

- Model RESSP
- **UL** listed
- Supplied with wall hanger
- Sodium Bicarbonate
- 12 year limited warranty

Proprietary low velocity nozzle design

Features

- Pressure gauge allows for immediate pressure status check
- Easy-to-pull safety pin
- Rust and impact resistant painted steel handle
- 2.5 lb. of fire extinguishing agent (Average)
- 12 year limited warranty
- UL approved wall hanger
- Powder coated aluminum cylinder is lightweight and corrosion resistant.



P/N: 21008173MTL - 6 pack UPC: 0-47871-27009-5 I2F - 10047871270092

P/N: 21008746MTL - 2 pack UPC: 0-47871-27009-5 I2F - 20047871270099

Product Specification

Product Specification	
Net agent weight (Average)	2,5 lb.
Unit weight (Average)	3.9 lb.
Diameter	3.25 inches
Height	14.20 inches
Discharge time	8-10 seconds
Discharge range	5 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Aluminum and steel
Wall hanger	Included

Packaging Options

Master Pack (6)	21008173MTL
Master Pack (2)	21008746MTL

Packaging dimensions (inches)

	Depth	Width	Height
Carton	3.375	4.375	14.375
Six Pack	9.1	14.75	10
Two Pack	9.4	15	4.10

*as of Jan. 2011. This information is subject to change without



1016 Corporate Park Drive, Mebane, NC 27302 (800) 880-6788 www.Kidde.com

