

5140MPS-1

Description:

- Manual Fire Alarm Box
- Single-action

Product advantages:

- Discrete, low profile – not a distraction from style and architecture
- Key reset
- Glass rod included
- Surface or flush-mount to maximize installation flexibility
- Simple, two-wire installation – minimizes installation cost and complexity
- Terminal connections
- Compatible with all fire alarm control panels

Recommended use:

A perfect fit for school classrooms, administration offices, retail areas, public libraries, payment centers and other locations where the general public is invited

Mounting recommendations:

- **Semi-flush mount:** Mount on single-gang electrical box
- **Surface mount:** Use 5140-BB Back Box

Compatibility:

Status output: Dry contact – all controls and zone input modules providing compatibility with dry contact output activation upon status change

Product dimensions:

4.74" H x 3.12" W x 2.0" D

Relay contact:

1A at 125VAC, 1A at 30VDC

Included items:

Two glass rods

Option available:

- 5140MPS-BB: Back Box
- SG-GR: Package of 10 extra Glass Rods

Listings:

- MEA
- CSFM Certificate Number: 7150-1645:118
- ADA Compliant

5140MPS-2



Description:

- Manual Fire Alarm Box
- Single-action

Product advantages:

- Discrete, low profile – not a distraction from style and architecture
- Allen wrench reset
- Glass rod included
- Surface or flush-mount to maximize installation flexibility
- Simple, two-wire installation – minimizes installation cost and complexity
- Wire lead connections
- Compatible with all fire alarm control panels

Recommended use:

A perfect fit for school classrooms, administration offices, retail areas, public libraries, payment centers and other locations where the general public is invited

Mounting recommendations:

- **Semi-flush mount:** Mount on dual-gang electrical box
- **Surface mount:** Use 5140-BB Back Box

Compatibility:

Status output: Dry contact – all controls and zone input modules providing compatibility with dry contact output activation upon status change

Product dimensions:

4.74" H x 3.12" W x 2.0" D

Relay contact:

1A at 125VAC, 1A at 30VDC

Included items:

Two glass rods

Option available:

- 5140MPS-BB: Back Box
- SG-GR: Package of 10 extra Glass Rods

Listings:

- MEA
- CSFM Certificate Number: 7150-1645:118
- ADA Compliant