14/2 STRANDED RISER SPEAKER CABLE, UNSHIELDED

14 AWG 2 Stranded Conductors

Ratings	CMR, CL3R, FT4
Approvals	ETL Listed

Construction

Conductor	14 AWG Oxygen-Free Bare Copper, 41-Stranded
Conductor Count	2
Insulation	Polypropylene (0.008" nom.)
Insulation Colors	Red, White
Lay Length	6" nom.
Shielding	N/A
Rip Cord	Yes
Jacket	PVC (0.017" nom.)
Overall Diameter	0.224" nom.
Print Legend	ADIPRO P/N RN-501XXXX OXYGEN FREE 2C14 3180662(ETL)US CL3R ROHS C(ETL)US CMR FT4 FOR AUDIO ONLY 500FT

Properties

Operating Voltage	300 Volts max.
DC Resistance	2.62Ohms/1000' at 20°C
Capacitance	24.6pF/ft. nom.
Impedance	62 Ohms nom.
Temperature	-20°C to 60°C
Flame Rating	UL 1666 (Riser); CSA C22.2 No. 2556 (FT4)
RoHS Compliant	Yes
Country of Origin	CHINA

PART#	COLOR	LENGTH	BOX
RN-5014501	WHITE	500FT	EXPRESS BOX

RoHS COMPLIANT

Intertek

For more information contact your ADI Sales person or visit adiglobal.com/adiexclusivebrands