22/4 RISER RATED, UNSHIELDED FIRE ALARM CABLE

22 AWG 4 SOLID CONDUCTORS

Ratings	FPLR, CL3R, FT4
Approvals	ETL Listed

Construction

Conductor	22 AWG Solid Bare Copper
Conductor Count	4
Insulation	Riser PVC (0.011" nom.)
Insulation Colors	Black, Red, Green, Yellow
Lay Length	Straight
Shielding	N/A
Rip Cord	Yes
Jacket	PVC (0.016"nom.)
Overall Diameter	0.123" nom.
Print Legend	ADI PRO P/N RN-2012506 OXYGEN FREE 4C22 3180662 (ETL)US FPLR 75C ROHS CL3R FT4 LOT#XXXX MMDDYY XXXXFT

Properties

Operating Voltage	300 Volts max.
DC Resistance	18 Ohms/1000'at 20°C
Capacitance	18.2 pF/ft.nom.
Temperature	-20°C to 75°C
Flame Rating	UL1666(Riser); CSA C22.2 No. 2556 (FT4)
RoHS Compliant	Yes
Country of Origin	China

PART#	COLOR	LENGTH	BOX
RN-2012506	RED	500FT	SPEED COIL

Intertek

For more information contact your ADI Sales person or visit adiglobal.com/adiexclusivebrands