Capture

PRODUCT SPEC SHEET

0E-22LED3

22" BNC FRAMELESS LED MONITOR

24/7/365 Operating Capability

The 22" BNC frameless LED monitor is designed to excel in 24/7 video surveillance applications. Delivering full HD resolution and 16.7 million colors, the monitor displays every detail with precision. HDMI and VGA inputs and a BNC input/output easily accommodate multiple devices and allow for BNC looping. The monitor also features source auto detection and quick touch scalability for quick setup.

FEATURES

- 21.5" Diagonal Viewing Size
- 1920x1080P Full HD Resolution
- 178° Ultra-Wide Viewing Angle
- Source Auto Detection
- Low Blue Light Technology
- Quick Touch Scalability 16:9/4:3
- BNC, VGA, HDMI and Audio Inputs
- Includes VGA, HDMI, Audio and Power Cables
- Two Built-In Speakers
- 30-Month Warranty

- Part #: 0E-22LED3
- UPC: 840049310490
- Length: 19.3" (490.2mm)
- Width: 8.6" (218.4mm)
- Height: 14.1" (358.1mm)
- Weight: 4.85 lbs. (2.19kg)
- UL Listed

FC CE RoHS COMPLIANT c UL us E505978 LISTED 5MH7

SELECT SERIES

FOR MORE INFORMATION, CONTACT YOUR ADI SALES PERSON.

Capture

FICHE SIGNALÉTIQUE

0E-22LED3

MONITEUR BNC À DEL SANS CADRE DE 22 PO

Capacité de fonctionnement 24/7/365

Le moniteur BNC à DEL sans cadre de 22 po est parfait pour les applications de vidéosurveillance en permanence. Grâce à une résolution HD intégrale et à ses 16,7 millions de couleurs, ce moniteur saura afficher tous les détails avec précision. Les entrées HDMI et VGA et une entrée/sortie BNC accueillir plusieurs appareils et permettre le bouclage BNC. Le moniteur est aussi doté de fonctionnalités de détection automatique de la source et de mise à l'échelle pour une configuration facile.

CARACTÉRISTIQUES

- Dimensions d'achage diagonales de 21,5 po
- Résolution HD intégrale 1920x1080 p
- Grand angle de vue de 178°
- Détection automatique de la source
- Technologie à faible lumière bleue
- Mise à l'échelle Quick Touch 16:9/4:3
- Entrées BNC, VGA, HDMI et audio
- Comprend des Câbles VGA, HDMI, audio et d'alimentation
- Deux haut-parleurs intégrés
- Garantie de 30 mois

- N° de pièce : 0E-22LED3
- UPC : 840049310490
- Longueur : 19,3 po (490,2 mm)
- Largeur : 8,6 po (218,4 mm)
- Hauteur : 14,1 po (358,1 mm)
- Poids : 4,85 lb (2,19 kg)
- Homologué UL

E505978 LISTED 5MH7

SÉRIE SELECT

POUR DE PLUS AMPLES RENSEIGNEMENTS, COMMUNIQUEZ AVEC UN REPRÉSENTANT ADI.

Capture

PRODUCT SPEC SHEET

0E-22LED3

TECHNICAL SPECIFICATIONS	
Model	0E-22LED3
Screen Diagonal Dimension (inches)	21.5"
Viewable Area W x H	18.8" x 10.2" (477.5mm x 259mm)
LED Type	Edge LED
Pixel Pitch (mm)	0.2493mm x 0.241mm
Screen Maximum Resolution	1920x1080
Display Resolutions	720x400; 640x480; 800x600; 1024x768; 1280x1024; 1366x768; 1920x1080
Supported Input Resolutions	720x400; 640x480; 800x600; 1024x768; 1280x1024; 1366x768; 1920x1080
Refresh Rate (hertz)	60Hz
Color Depth (millions)	16.7 million colors
Brightness	250 nits (250 cd/m^2)
Auto Adjust	Yes
Monitor Aspect Ratio	16:9
Display Aspect Ratio	OSD options: Full/4:3/Over Scan
Horizontal TV Lines	1080
Contrast Ratio	4000:1SCR
Response Time (ms)	5 ms (GTG)
View Angle H/V (degrees)	178° x 178°/CR＞10
Digital Video Inputs	HDMI up to 1920x1080
Analog Video In/Out	VGA up to 1920x1080
Connector	HDMI x 1 , VGA x 1 , BNC IN x 1 , BNC OUT x 1 , AUDIO OUT x 1
Audio Inputs (stereo)	1 x 3.5mm mini-jack
Speakers (watts)	2 x 2 watts
Stand-by (watts)	＜0.5 watt
Power Consumption (watts)	16 watts typical
Monitor Body Dimensions	19.3" x 1.5" x 11" (490.2mm x 38.1mm x 279.4mm)
Dimensions Monitor+Stand	19.3" x 8.6" x 14.1" (490.2mm x 218.4mm x 358.1mm)
Panel Surface	Matte black
Case and Stand Material	Plastic
VESA Mounting Pattern (mm)	100mm x 100mm
Base/Stand Included	Yes
Base Tilt Angle	-5°~15°
Weight Cabinet Only	4.08 lbs. (1.85kg)
Weight Cabinet+Base Stand	4.85 lbs. (2.19kg)
Power Supply (internal)	AC 100-240V~50/60Hz 1.1A
Operating Temperature	0°C~40°C / 32°F~104°F
Storage Temperature	-20°C~50°C / -4°F~122°F
Operating Humidity	10~90%
Accessories Included in the Box	Power cable/HDMI cable/VGA cable/Audio cable/IR Remote Stand support/Screws/Base of stand/User manuals
Mounting Screw Size (mm)	M4-L8 mm/4pcs
Certifications	CE/FCC/RoHS/HDMI/UL/WEEE/REACH
Warranty	30 Months

SELECT SERIES

FOR MORE INFORMATION, CONTACT YOUR ADI SALES PERSON.