Specifications

Eaton 9SX3000G

Catalog Number: 9SX3000G

Eaton 9SX online, extended runtime UPS, 3000 VA, 2700 W, L6-20P input, Outputs: (1) C19, (8) C13, 13.6"Hx8.4"Wx16.2"D, 77.2 lb., network card optional

General specifications

Product Name Eaton 9SX UPS	Catalog Number 9SX3000G
UPC 743172091314	Product Length/Depth 16.2 in
Product Height 13.6 in	Product Width 8.4 in
Product Weight 77.2 lb	Warranty 3 year limited
Compliances FCC Compliant CE Marked	Certifications cULus Listed

Powering Business Worldwide

Battery

Runtime graph

View runtime graph

Battery management

ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)

Battery replacement

Hot-swappable internal batteries and extended battery modules (EBMs)

Extended battery capability

Yes

Electrical output

Receptacle

(1) C19, (8) C13

Topology

Online/Double-conversion

Wattage

2700 W

VA rating

3000 VA

Output waveform

True sine wave

Voltage

208 V

Output power factor

0.9

Output nominal voltage

208V default (200/208/220/230/240/250V)

Output frequency

50/60 Hz

Feed type

1

Electrical input

Input connection

L6-20P

Input cord length

8 ft

Input frequency range

60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz

Input power factor

>.99

Communications

Communication

(1) MiniSlot
(1) USB port
(1) Serial RS-232 port
(1) RPO/ROO/Signal input terminal
(1) mini-terminal block for output relay

Expansion slots

(1) Mini-Slot (MS) expansion port. Optional connectivity cards may be ordered separately.
- Gigabit Web/SNMP card

part number: NETWORK-M3
- Modbus card part number: INDGW-M2
- Relay card part number: RELAY-MS

User interface

5-button graphical user interface

Potential free switch contact

Yes

Environmental

Temperature range

0° to 40°C (32° to 104°F)

Additional specifications

Form factor

Tower

Construction type

Free standing model

Package contents

9SX 3000 VA UPS
Quick start guide
(2) IEC C13-C14 jumpers 1.8m
8-foot C19 to L6-20P input connector
RS-232 serial cable
USB cable

Internal bypass

Yes

Warranty and support

Standard factory warranty

3-YEAR FACTORY WARRANTY
- 3 years
- Parts, electronics and batteries coverage
- Standard ground shipping
- Technical support

Extended service plans

ADVANCED DEPOT EXCHANGE
- 5-year depot repair: 9SW5Y-3000UC
- Expedited parts coverage for 5 years
- Parts, electronics and UPS

Resources

Brochures

Eaton 9SX UPS installation and user manual

Eaton 9SX UPS visio stencils

Eaton 9SX UPS technical specifications

Eaton 9SX UPS brochure

Certification reports

EC DoC Eaton 9SX

Characteristic curve

9SX3000G ups-battery-runtime graph

Drawings

9SX3000G UPS 2D technical drawing

9SX3000G UPS 3D technical drawing

Manuals and user guides

Quick start guide for Eaton 9SX UPS 208V models

batteries coverage
- Next business day shipping
- Technical support
5-YEAR ON-SITE PLAN: WFLN75XX-6009UC
- On-site parts and labor coverage for years 5
- Parts, electronics and UPS batteries coverage
- 24x7 on-site labor coverage, next-day response
- Next-day shipping
- Technical support

Specifications and datasheets

Eaton Specification Sheet - 9SX3000G

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia